

On The Go® Portable Water Softener

First Time Hookup Installation Instructions

- Step 1: Turn off the water feeding the point of application.
- Step 2: Connect the source water to the inlet of the softener.
- Step 3: Make sure the unit is standing upright for use.
- Step 4: Turn the water on and flush system into a drain for 2-3 minutes for the Standard, 4-6 minutes for the Double Standard, and 7-9 minutes for the Park Model Water Softener.
- Step 5: Connect the outlet of the softener to the point of application.
- Step 6: Your unit is ready for use.

Note: The softener does not require salt or regeneration before first use. **DO NOT** remove the material from inside the tank.

Regeneration Instructions

- Step 1: Turn off water supply.
- Step 2: Disconnect outlet house.
- Step 3 (optional/see back): Drain water by tilting unit over or turning it upside down with the head/cap **ON**.
- Step 4: Remove top cap.
- Step 5: Add the correct amount of salt into the top cap for your model:
 - One full 26 oz. box of iodized or non-iodized salt for the Standard model.
 - Two full 26 oz. boxes of iodized or non-iodized salt for the Double Standard Model.
 - Four full 26 oz. boxes of iodized or non-iodized salt for the Park Model Water Softener.

In extremely hard conditions, also use 1-2 teaspoons of Super Iron Out for the Standard Model, 2-4 teaspoons for the Double Standard Model, and 4-6 teaspoons for the Park Model Water Softener.
- Step 6: Replace cap and turn the water on and rinse very slowly for the directed amount of time.
 - Rinse for 12-15 minutes for the Standard Model.
 - Rinse for 24-30 minutes for the Double Standard Model.
 - Rinse for 50-60 minutes for the Park Model Water Softener.

Note: Stream of water should just clear the side of the tank.

- Step 7: Increase water flow to fast-rinse.
 - Rinse for 3-4 minutes for the Standard Model.
 - Rinse for 6-8 minutes for the Double Standard Model.
 - Rinse for 10-12 minutes for the Park Model Water Softener.
- Step 8: Test with the hardness test strips the water at the **OUTPUT** of the softener to make sure it's down between 0-2 GPG.
- Step 9: Regeneration cycle is complete.

Back-Flush Instructions

Back flush your Standard Softener every 3 months for 2-5 minutes, Double Standard Softener for 5-10 minutes, and 10-15 minutes for the Park Model Water Softener.

- Step 1: Turn off water and disconnect both inlet and outlet hoses.
- Step 2: Use the female/female adapter (not labeled) to the outlet of the softener.
- Step 3: Connect the water source to the softener outlet.
- Step 4: Turn the water on full stream. (If the flow completely stops, turn the water off, tap the tank against the ground to get the resin to fall back down, and turn the water on 75% full stream.)
- Step 5: After the recommend amount of time, turn the water off and hook the softener back up.

Note: If Back-flush and Re-gen are done together, perform the Back-flush process first.

Draining Instructions

You can use either of these two options if draining water from the unit is required. For both options **DO NOT REMOVE** top cap or head.

Step 1: Turn the unit upside down and allow water to drain from inlet/outlet.

Step 2: Use air source applied to inlet and allow water to drain from outlet.

Storage Instructions

Before placing the unit in storage or being idle for extended periods:

Step 1: Perform the regeneration process.

Step 2: Drain water from unit (**do not dump the resin out**).

Step 3: Unit is ready for storage.

Post Storage Instructions

After extended periods of non-use, sanitize the unit by following the instructions below:

Step 1: Perform back flush.

Step 2: Completely drain all the water from the tank.

Step 3: Remove top cap and mix 1/4 packet of Sani-System with a gallon of water for the Standard Model, 1/2 packet of Sani-System with 2 gallons of water for the Double Standard Softener, or 1 full packet of Sani-System with 4 gallons of water for the Park Model Water Softener.

Step 4: Pour solution into tank, put the top cap back on, and let it sit for a maximum of 60 seconds.

Step 5: Turn the water on full stream for 10 minutes and flush the Sani-System out.

Step 6: Perform regeneration.

**DO NOT DUMP THE RESIN OUT
OF THE TANK!**

www.portablewatersoftener.com